

Versatus[™]



Smooth venous access Better comfort for the patient



ultra-snarp triple bevel that minimizes patient discomfort and tissue trauma. The gently tapered catheter tip aligns with the needle bevel to provide smooth transition from needle to catheter during insertion. Additionally the production of VersatusTM IV Catheter is computer-controlled to maintain a constant, minimum distance from needle heel to catheter tip. This permits a smooth insertion even into small vessels while reducing the risks of penetrating the posterior wall of the vein.

Material

To ensure minimum discomfort for the patient this catheter is made of polyurethane (PUR) which is firm at room temperature and softer at body temperature, kink resistant and biocompatible.



Convenient rigid, colour-coded case

Each Versatus™ IV catheter is individually packed in a sterile, easy-toopen plastic case. This rigid plastic case provides added protection to both the catheter and the user. The case is colour-coded for easy indentification of the catheter gauge and has a tamperevident seal for additional safety.



Obturator

A luer-lock obturator is available for each catheter gauge (except 24G). This obturator efficiently prevents thrombous formation in the lumen of the catheter when the infusion is interrupted. The obturator is colour-coded in accordance with the catheter to avoid confusion.

Needle bevel indicator

The mark on the upper surface of the flashback chamber serves as a needle bevel indicator. This permits precise bevel alignement even after venipuncture has been initiated.



Rapid flashback confirmation

The flashback chamber is fully transparent for immediate confirmation of venipuncture. The incorporated hydrophobic membrane filter allows air to vent easily with virtually no resistance, which results in a rapid blood return even in the smaller gauge sizes.






Versatus™	EN/ISO colour code	External catheter diameter		Internal catheter diameter	Catheter	Flow rate ml/min	Obturator
References		Gauge	mm	mm	length mm	1111/111111	
SR*OF2419	Yellow	24	0.67	0.47	19	15	
SR*OF2225	Blue	22	0.85	0.60	25	38	SO-2225F
SR*OF2032	Pink	20	1.10	0.80	32	67	SO-2032F
SR*OF2051	Pink	20	1.10	0.80	51	59	SO-2051F
SR*OF1832	Green	18	1.30	0.95	32	99	SO-1832F
SR*OF1851	Green	18	1.30	0.95	51	88	SO-1851F
SR*OF1651	Grey	16	1.70	1.30	51	184	SO-1651F
SR*OF1464	Orange	14	2.17	1.73	64	282	SO-1464F



Every day, as healthcare professionals, you are working to ensure life and to contribute to the well-being of your patients. Every day, Terumo Europe provides you with the clinical systems, means and solutions to keep life flowing.



We keep life flowing

TERUMO CORPORATION 44-1, 2-chome

Shibuya-ku Tokyo 151 JAPAN Tel. +81/3 3374.8111 Fax +81/3 3374.8196

TERUMO EUROPE N.V.

Researchpark Zone 2 Haasrode Interleuvenlaan 40 B-3001 Leuven BELGIUM Tel. +32/16.38.12.11 Fax +32/16.40.02.49

TERUMO EUROPE N.V. BENELUX SALES DIVISION

BENELUX SALES DIVISION Researchpark Zone 2 Haasrode Interleuvenlaan 40 B-3001 Leuven BELGIUM Tel. +32/16.38.14.02 Fax +32/16.38.15.55 THE NETHERLANDS Fax +0800/022.34.89

LABORATOIRES TERUMO FRANCE S.A.

1, Parc Ariane Bâtiment Uranus Batiment Uranus Rue Hélène Boucher 78284 Guyancourt Cedex FRANCE Tel. +33/1 30.96.13.00 Fax +33/1 30.43.60.85

TERUMO (DEUTSCHLAND) GmbH

Lyonerstrasse 11 a 60528 Frankfurt am Main GERMANY Tel. +49/69.66.44.20 Fax +49/69.66.66.826

TERUMO EUROPE SUCURSAL EN ESPAÑA Avenida de Burgos 16-D Edificio EUROMOR Madrid 28036 ESPAÑA Tel.+34/91 383.90.69 +34/91 383.91.61 Fax+34/1 767.04.60

TERUMO EUROPE ROME BRANCH

BRANCH Via Simone Martini 143/145 I-00142 Roma ITALIA Tel.+39/06.519.61.420 Fax+39/06.503.04.07

TERUMO EUROPE N.V.

Belgien fillal Sverige Nya Varvet Byggnad 90 SE-426 71 Västra Frölunda SWEDEN Tel. +46/31.748.58.80 Fax +46/31.748.58.90

TERUMO U.K. (Branch of Terumo Europe N.V.) 3 Unity Grove Off School Lane Knowsley Industrial Park South Knowsley UNITED KINGDOM Tel. +44/151.482.4800 Fax +44/151.482.4811

®: Registered Trademark Published by Terumo Europe N.V.

www.terumo.com www.terumo-europe.com